

# PHILIPS

6 inch LED light bar  
set (x2)

Ultinon Drive 2000

Road-legal ECE R149-10

2000 lm, +270m beam length

LED position-light function

All terrain, all weather

LUMUD2001LX2



## Boosted visibility brings safer driving Extra brightness for everyday use

See far and wide with crisp, white light projected up to 270 meters. The Ultinon Drive 2001L LED light bar is 100% road-legal with a tough, one-piece design integrating advanced cooling tech. It shrugs off water, dust, rust and impacts.

### **Boosted visibility makes you safer on the road**

- Extra brightness for superior visibility

### **Be noticed with additional position lights**

- Extra position lights that get you noticed

### **Built to withstand difficult driving conditions**

- Robust design for tough environments

### **Robust design for challenging conditions**

- Corrosion-free, stainless-steel mounting brackets

### **Road-legal auxiliary lights**

- Powerful road-legal LED light bars

# Highlights

## Bright LED position lights

Try our Philips Ultinon Drive 2001L LED light bar with position lights, and you'll never go unnoticed on side roads or in parking areas.

## Built for tough environments

The Philips Ultinon Drive 2001L LED light bar is built to withstand tough conditions throughout your journey. It is shock-resistant (IK07-rated) to ensure faultless performance on and off the road, with an unbreakable polycarbonate lens. It can handle immersion in water (IP67-rated) to provide reliable illumination for your overland adventures, wherever your trail leads.

## Corrosion-free brackets

The mounting brackets for the Philips Ultinon Drive 2001L LED light bar are made of stainless steel, which is corrosion-free. They can withstand snow, ice and even salt. Built

from durable, high-quality materials, your Philips auxiliary LED lights will provide years of reliable service.

## Road-legal LED lights

The Philips Ultinon Drive 2001L series meets ECE-R149 standards and is 100% road-legal for high-beam and position-light functions. For added safety, Philips LED light bars are tested to EMC R10 specification to ensure they will function smoothly with your vehicle's electrical systems.

## Up to 270-meter visibility

The Philips Ultinon Drive 2001L LED light bar gives you extra high-beam brightness to illuminate the road ahead for up to 270 meters\*. Producing 2000 lumens (effective), our LED lightbar complies with ECE-R149-10 and provides ample visibility ahead and at the road's edges for faster reactions. Its cool light color of 6500 Kelvin creates better contrast and keeps drivers focused.

# Specifications

## Electrical characteristics

**Voltage:** 9-30 Volt DC

## Light characteristics

**Beam length 1 lux-m:** 270

**Beam pattern:** Combo beam

**Color temperature:** 6000 K K

**Effective lumen output:** 2000 lumens

**Raw lumen output:** 3270 lumens

**Beam length 3 lux-m:** 140

## Ordering information

**GOC:** 01832894

**Order entry:** UD2001LX2

## Packaging Data

**EAN1:** 8719018018328

**EAN3:** 8719018018335

## Packed product information

**Box dimensions-L(mm):** 180

**Box dimensions-W(mm):** 150

**Box dimensions-H(mm):** 80

**MOQ (for professionals):** 4

**Number of product in the box:** 2 lamps

**Gross weight box-g:** 1138±36

**Net weight product-g:** 1138±36

## Product description

**Boost function installation:** No

**Boost mode activation:** No

**Break resistance**

**Corrosion protection:** Yes, aluminum powder coated

**corrosion-free brackets:** Side mounting brackets

**ECE R10**

**ECE R148**

**ECE R149**

**ECE reference number:** 10

**Heat sink:** Aluminum powder coated die-cast

**Impact protection rating (IK):** IK07

**Ingress protection rating (IP):** IP67

**Installation angle:** 360°

**Material:** Aluminum die-cast

**Number of LEDs:** 16x 5W, 6x 5W

**Offroad boost:** No

**One-piece body design**

**Operating temperature:** -40° C to 65° C

**Parking position light**

**Plug type:** 3-pin DT Connector with 0.5m cable

**Range:** Ultinon Drive 2000

**Scratch resistant lens**

**Technology:** LED

**Width:** 163 mm / 6 inch

