

PHILIPS

20 inch LED lightbar

Ultinon Drive 5100

Road-legal ECE R149 - 30+30

4000 lm, 500 m beam length

Dual-color position light

All terrain, all weather

LUMUD5103LX1



Powerful brightness driving safety at the wheel

Bright, durable gear for overland journeys

The Philips Ultinon Drive 5103L LED light bar has the power to keep you safer, wherever you're headed. Spot hazards up to 500 meters away with lighting that performs in the most hostile environments and gives your vehicle a touch of style.

Brilliance that makes you a safer driver

- Intense, far and wide illumination for superior visibility

Dual-color position lights that get you noticed

- Choose your position-light color

Designed to handle hostile environments

- Corrosion-free body, stainless-steel mounting brackets
- Sturdy one-piece body for tough environments
- IP68 & IP69K waterproof to master the elements

Road-legal auxiliary lights

- Powerful road-legal LED lightbars

Easy to install with flexible mounting options

- Low-profile design for simpler fitment

Highlights

Up to 500-meter visibility

The Philips Ultinon Drive 5103L LED light bar provides a brilliant light beam that illuminates the road ahead for up to 500 meters*. Its effective 4000 lumens are homogeneously distributed in an optimized indirect beam, generating intense illumination far and wide with reduced glare for everyday use. This enables drivers to react faster on dark, rural and dirt roads. Its cool light color of 6500 Kelvin produces daylight conditions, improving contrast and helping drivers stay focused.

Brilliant-white or -amber LED

Never go unnoticed on side roads or in parking areas with the extra LED position lights of our Philips Ultinon Drive 5103L. Express your style and personality by choosing your light color, either intense amber or cool white.

Sturdy one-piece body

The Philips Ultinon Drive 5103L LED light bar is built in a single piece to withstand the toughest conditions. Its design provides excellent heat management and consistently high light output throughout your journey. Rated IK07, it is shock-resistant to ensure faultless performance on and off the road. Its unbreakable polycarbonate lens can take any hit without damage or scratches.

Waterproof for durable light

With its ingenious screwless design, the Philips Ultinon Drive 5103L LED light bar can withstand the wettest conditions. Its IP69K

certification means it will perform, wherever your road leads and whatever the weather. And it will be more than a match for any power washer you use to clean your car afterwards.

Corrosion-free

With its anodised pre-treated and automotive-grade powder-top-coat body, the Philips Ultinon Drive 5103L LED light bar offers ultimate corrosion protection. Its mounting brackets are made of stainless steel, which is corrosion-free. It can withstand snow, ice and even salt. Built from durable, high-quality materials, your Philips auxiliary LED lights will provide years of reliable service.

Road-legal lights

The Philips Ultinon Drive 5103L LED light bar meets ECE standards and is 100% road-legal for high-beam and position-light functions. It can be installed individually and centrally on vehicles, and still be ECE-compliant thanks to its twin light-module design in a single bar.

Easy and flexible installation

The sleek, low-profile design makes installation easier, and flexible fitment options are possible with side-mounting brackets (included) and back-mounting brackets (UD1001M optional). Supplied with a pre-wired male/female 4-pin superseal DT connector, it is voltage-overload and reverse-polarity protected to make installation secure and easy.

Specifications

Electrical characteristics

Voltage: 9-30 Volt DC

Product description

Accessories (optional): LUMUD1001M, LUMUD1003W, LUMUD1004W

Boost function installation: No

Boost mode activation: No

Break resistance

corrosion-free brackets: Side mounting brackets

ECE R10

ECE R148

ECE R149

ECE reference number: 30

Impact protection rating (IK): IK07

Ingress protection rating (IP): IP68 & IP69K

Installation angle: 360°

Material: Aluminum extruded

Offroad boost: No

One-piece body design

Operating temperature: -40° C to 80° C

Parking position light: Yes, white or amber

Range: Ultinon Drive 51000

Plug type: 4-pin DT Connector with 0.5m cable

Scratch resistant lens

Technology: LED

Width: 558 mm / 20 inch

Light characteristics

Beam length 1 lux-m: 500

Color temperature: 6500 K K

Effective lumen output: 4000 lumens

Raw lumen output: 19800 lumens

Packed product information

Box dimensions-L(mm): 610

Box dimensions-W(mm): 105

Box dimensions-H(mm): 90

MOQ (for professionals): 4

Number of product in the box: 1 lamp

Ordering information

GOC: 01846594

Order entry: UD5103LX1

Packaging Data

EAN1: 8719018018465

EAN3: 8719018018472

Outerpack information

Height: 230 cm

Length: 630 cm

Width: 200 cm

